

Technical Data Sheet

Jacor Thinner GP Acrylic Lacquer

JCR-81100

Product Information

General purpose thinner for industrial pigmented paints and dyes. Used for thinning of industrial solvent based paints, nitrocellulose paints, thinning epoxy paints, and dilution of solvent based wood stains .

Description: Special formulation of high purity organic solvents .

Features:

- Paint flow enhancement
- Paint viscosity reduction
- Gloss retention
- Smooth tactile retention
- Pore-filling enhancement

Product Characteristics

Composition: liquid solvent

Properties:

- Excellent Dissolver
- Moderate evaporation speed
- Transparent

Application Information

Versatility:

- Thinning
- Cleaning
- Diluting

Intended Uses: Thinner for various solvent based industrial pigmented paints .

Functionality: Optimising paint application by reducing viscosity, enhancing flow, maintaining glossiness, and facilitating the paint to pore-level filling for a uniform finish.

Application Methods: Adding the necessary quantity following the product's recommended thinning ratio to achieve required viscosity for its application.

Storage and Safety

Storage Condition: Store in a cool, dry place away from heat sources and open flames .

Shelf Life: Remains effective for 18 months post initial opening, in securely closed and appropriate storing conditions .

Special Precaution: Use appropriate personal protective equipment (PPE). Avoid contact with skin and eyes. Use in a well-ventilated area . The product is flammable. Close the can after usage. Keep away from children.

Health and Safety: In case of insufficient ventilation during application, wear suitable respiratory equipment. Do not inhale the vapour / spray. In case of contact with eyes, rinse immediately with plenty of fresh water and seek medical assistance .

Technical Specifications

- **Density:** 0.82 ± 0.03 g/cm³ at 25°C

Attributes and Variants

Size Variants: Volume in Litres (17 Litres, 4 Litres, 1 Litres)